

Prime X[®] X-ray Stretcher



Image quality. Access. Versatility.

Prime X Stretchers offer the safety and efficiency of Stryker's Prime Series stretcher, with the ClearView Technology platform. The unique dual-deck design of the patient platform allows positioning of cassettes at any point under the patient, from head to foot and side to side. Open architecture accommodates virtually any size of cassette. This versatile solution helps caregivers deliver exceptional patient care throughout the hospital by combining a mobile platform with ClearView Technology enabling quality imaging.



Clearview Technology

Our Prime X X-ray Stretcher, utilizing ClearView Technology in a dual-deck design, offers a similar image quality to an X-ray table with the convenience and efficiency of a mobile platform.



Advanced mobility option

Big Wheel Advanced Mobility
Reduces start-up push force up to 50% and steering up to 60% when compared to the average 5th wheel stretcher.¹

Zoom Motorized Drive System
Virtually eliminates manual pushing.



Simple cassette positioning

The unique dual-deck design with an open cassette platform and a full 360° of access allows positioning of cassettes from head end to foot end and side to side. Open architecture accommodates virtually any size cassette.

Optional integrated scales help reduce patient transfers and make patient care efficient.

Electric lift makes raising the stretcher easy by simply stepping on the pedal.

700 lb. weight capacity accommodates bariatric patients.

Articulating backrest and foot section allows complete access to the dual deck for easy cleaning.

Glideaway siderails provide exceptional coverage and tuck neatly under the litter deck for unobstructed lateral imaging and storage when you don't need them.

Stryker's Prime X X-ray Stretcher exclusively uses a red color scheme on its handles, siderails, bumpers and accent rings, so the X-ray stretcher is **easily identified**.

1. Hospital Focuses on Mobility with Big Wheel, 2005.

Prime X X-ray Stretcher



Standard features

- Clearview Technology Platform
- Thermoformed ABS base with extra capacity storage tray
- 700 lb. weight capacity
- 30-inch wide patient surface with 3-inch Enhanced Comfort Support Surface
- Litter-mounted oxygen bottle holder
- Integrated transfer board
- Power-washable design (1105X and 1115X only)
- Four-wheel, center-locking brake system with dual end activators
- Dual, side-mounted foot control hydraulics with uni-lower pedal
- Glideaway Siderails
- 4 integrated IV receptacles
- +/- Trendelenburg
- 8-inch Omni Surface Casters with integrated wheel covers
- Pneumatic backrest/stationary foot
- Constant descent hydraulics
- Dual end brake/steer controls

Warranty

Two years parts, labor and travel

Optional features

- 4" (10 cm) enhanced comfort support surface
- 4" (10 cm) or 5" (13 cm) Ultra Comfort Support Surface
- Four-sided brake and steer controls (1105X and 1115X only)
- Pop-up push handles (1105X and 1115X only)
- Integrated scale system
- Three-sided hydraulic controls (1105X and 1115X only)
- Foot-end push handles (1105X only)
- Dual-ended siderail release
- Footboard/chartholder
- IV caddy
- Serving tray
- IV poles
 - Permanent folding two- or three-stage at foot end
 - Removable
- Serving tray holder/footboard
- Siderail pads
- Upright oxygen bottle holder
- Restraint straps
- Retractable cord reel
- Powered lift (1105X and 1115X only)
- 120V or 240V available
- Lateral cassette holder
- Upright cassette holder
- Defibrillator tray
- Defibrillator tray/foot extender/charting surface

Specifications

Model number	1105X (Prime X Stretcher with Fifth Wheel)* 1115X (Prime X Stretcher with Big Wheel Advanced Mobility)* 1125X (Prime X Stretcher with Zoom Motorized Drive System)*
Overall length	
1105X and 1115X	85" (215.9 cm)
1125X	86" (218.4 cm)
Overall width	
Siderails up	38" (96.5 cm)
Siderails down (1105X and 1115X)	30.5" (77.5 cm)
Siderails down (1125X)	30.5" (77.5 cm)
Patient surface	30" x 75.25" (76 x 191 cm)
Weight capacity	700 lb. (318 kg)
Height range	
High (1105X and 1115X)	36.5" (92.7 cm)
High (1125X)	34" (86 cm)
Low (1105X and 1115X)	23.25" (59.1 cm)
Low (1125X)	23" (58 cm)
Litter positioning	
Backrest	0°-90° (±5°)
Trend./Reverse Trend. (1105X and 1115X)	±17° (±3°)
Trend./Reverse Trend. (1125X)	±16°
Siderails	14" x 57.75" (36 x 147 cm)
Caster diameter	8" (20 cm)
EMC	IEC 60601-1-2

3800 E. Centre Avenue
Portage, MI 49002 USA
t: 269 329 2100
toll free: 800 327 0770

patienthandling.stryker.com

*Options not available in all countries. Please contact your local country representative to learn of availability in your area. Stryker reserves the right to change specifications without notice. Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: **Big Wheel, Clearview Technology, Prime X, Stryker, Zoom**. All other trademarks are trademarks of their respective owners or holder.

Copyright © 2017 Stryker
Mkt Lit-626 13 DEC 2011 Rev D.4